

Copyright is owned by the Author of the thesis. Permission is given for a copy to be downloaded by an individual for the purpose of research and private study only. The thesis may not be reproduced elsewhere without the permission of the Author.

ZigBee-Based System for Remote Monitoring and Control of Switches

A thesis presented in partial fulfilment of the requirements for the degree of

Master of Engineering

at Massey University, Albany,

New Zealand.

© Matthew Lyon

October 2010

Abstract

Home automation technology has existed for nearly four decades, but is nonetheless mostly absent in the average home today. The systems that do exist are often highly customised and expensive, catering to a very niche market, or overly sophisticated and complicated. Many of these also require extensive, dedicated cabling as their communications backbone and as such are only practical to install during the construction of a new house.

The core aims of this project are to develop a cheap and simple home automation system that can be easily installed in new and existing houses. These aims are achieved by creating a centralised system where most of the intelligence is managed by a PC server and the end nodes are kept as simple as possible.

The server is responsible for basic security, maintaining awareness of the current system state and providing the user interface. At the outer edge of the system is a ZigBee network of wall switches and, in between, a home gateway provides a protocol translation service between the two. The new, “smart” switches are designed to be entirely compatible with existing wall switches in terms of their mounting and wiring requirements, and so ZigBee is chosen to provide a reliable wireless communication channel between the end nodes and the gateway.

Development of the system is undertaken in three stages; design of the server software (including the user interface and server processes), design of the home gateway embedded software, and design of the hardware and embedded software of the switches.

The end result is an effective, entry-level system that provides the benefits of remote management without the need for a costly or complex infrastructure.

Acknowledgements

A number of people have made a valuable contribution to this thesis through their support, guidance and help with various technical problems.

Many thanks are extended to Jamie McIntyre for his assistance with the use of Altium, and sound advice during the design and production of the switch hardware.

I also gratefully acknowledge Reece McCarthy, long-time friend and electrician, for lending his knowledge and experience in mains wiring and existing smart house products.

To my parents, many thanks for your endless motivation and support, especially in the final stages.

And finally, this project owes much of its success to the support and guidance of supervisor, Dr Tom Moir, whose direction throughout the process of developing and writing has been hugely appreciated.

Table of Contents

Abstract	2
Acknowledgements	3
List of Tables	8
List of Figures	9
1 Introduction	10
1.1 Project Overview.....	10
1.2 Design Specification	11
1.2.1 Requirements	11
1.2.2 Constraints	13
1.3 Thesis Outline	13
2 Literature Review	15
2.1 Problems Facing the Home Automation Industry.....	15
2.2 Existing Technologies	16
2.2.1 X10 and INSTEON.....	16
2.2.2 CEBus and C-Bus	16
2.2.3 Vantage	17
2.2.4 Control4	17
2.2.5 KNX.....	18
2.3 Research Approaches	18
2.4 Standards	19
2.4.1 OSGi	19
2.4.2 ZigBee.....	20
2.5 Summary	21
3 System Design	22
3.1 Project Framework	22

3.1.1	Remote Switching Process.....	23
3.1.2	Local Switching Process	23
3.2	Communication Protocol.....	24
3.2.1	Command Messages	25
3.2.2	Data Messages	25
3.2.3	Notification Messages.....	25
3.2.4	Acknowledgement Messages.....	26
3.2.5	Server Disconnect Signal.....	26
3.2.6	Command Mode Protocol.....	26
3.2.7	Communication Overview	27
4	Server Design	28
4.1	User Interface	28
4.1.1	Security	28
4.1.2	User Authentication	29
4.1.3	Control Centre.....	30
4.1.4	Switchboard	31
4.1.5	Alert Boxes	33
4.1.6	System Management.....	33
4.1.7	Event History	36
4.2	Database	37
4.2.1	Users Table	37
4.2.2	Devices Table.....	38
4.2.3	History Table	40
5	Home Gateway Design.....	42
5.1	Programming the Microcontroller.....	42
5.1.1	Microchip TCP/IP Stack	42
5.2	TCPHandler Module	42

5.2.1	Handler States	43
5.2.2	Managing Error Situations.....	43
5.3	UHandler Module.....	45
5.3.1	Handler States	45
5.3.2	Receiving Serial Data	45
5.3.3	Notifying the Server.....	46
5.4	LCD Display	46
5.5	Gateway Architecture.....	47
6	Switch Design.....	49
6.1	First Switch: Hardware Design	49
6.1.1	Power Supply	50
6.1.2	LED Indicators.....	51
6.1.3	Programming Header	51
6.1.4	Reset Button.....	52
6.1.5	ZigBee Module Pin Connections	52
6.1.6	PIC18F1220 Microcontroller Pin Connections	52
6.2	First Switch: Software Design.....	53
6.2.1	Initialisation	53
6.2.2	Interrupt Service Routines	54
6.2.3	Main Software Loop	55
6.2.4	Design Shortcomings	56
6.3	Switch Two: Hardware and Software Refinements	57
6.3.1	Power Supply	58
6.3.2	Switch Button as External Interrupt.....	60
6.3.3	Switch Announcement	61
7	Development and Testing	62
7.1	High Level Overview	62

7.2	System Development and Testing.....	64
7.3	ZigBee Performance Testing.....	65
8	Conclusions and Future Work	67
8.1	Conclusions	67
8.2	Future Work	68
	References.....	71
	Appendix.....	74
A.	Circuit Schematics	74
B.	Web Server Source Code.....	76
B.1	login.html.....	76
B.2	login.php	78
B.3	mainpage.php.....	79
B.4	switchboard.php.....	80
B.5	manage_system.php.....	83
B.6	add_device.php	87
B.7	add_user.php.....	89
B.8	show_history.php.....	91
C.	Server Processes Source Code	94
C.1	server_actioner_cgi.c	94
C.2	server_listener.c	100
D.	Gateway Source Code	106
D.1	TCPHandler (TCPH.c)	106
D.2	UHandler.c.....	112
E.	Switch Firmware Source Code	115
E.1	Switch 1 (End_device/ex1.c).....	115
E.2	Switch 2 (End_device2/ex1.c).....	119

List of Tables

Table 4.1: MySQL description of <i>auth_users</i> table	37
Table 4.2: MySQL description of <i>devices</i> table	38
Table 4.3: MySQL description of <i>history</i> table	41
Table 5.1: LED variable assignments	44

List of Figures

Figure 3.1: <i>Project framework</i>	22
Figure 3.2: <i>server_listener output</i>	24
Figure 3.3: <i>Space-time diagram of system communications</i>	27
Figure 4.1: <i>Main MAMP window</i>	28
Figure 4.2: <i>Certificate Warning (Internet Explorer 8)</i>	29
Figure 4.3: <i>Address bar indications for certificate error and secure browsing (Internet Explorer 8)</i>	29
Figure 4.4: <i>Login window</i>	30
Figure 4.5: <i>Control centre options for admin user</i>	31
Figure 4.6: <i>Typical switchboard display</i>	32
Figure 4.7: <i>Offline switch indication</i>	32
Figure 4.8: <i>JavaScript alert box</i>	33
Figure 4.9: <i>System management page</i>	34
Figure 4.10: <i>Devices table with completed form data</i>	34
Figure 4.11: <i>JavaScript confirmation box</i>	35
Figure 4.12: <i>Users table</i>	35
Figure 4.13: <i>Event history page</i>	36
Figure 5.1: <i>LEDs located below the LCD display</i>	44
Figure 5.2: <i>LCD display at start-up</i>	47
Figure 5.3: <i>Gateway architecture</i>	48
Figure 6.1: <i>Mounting box</i>	49
Figure 6.2: <i>PCB layout of first switch</i>	50
Figure 6.3: <i>Completed hardware assembly of first switch</i>	53
Figure 6.4: <i>General architecture of second switch</i>	57
Figure 6.5: <i>PCB layout of second switch</i>	58
Figure 6.6: <i>Circuitry removed from PowerTech Plus Plugpack</i>	58
Figure 6.7: <i>Various assemblies of the second switch</i>	59
Figure 7.1: <i>Logical system architecture</i>	62
Figure 7.2: <i>Physical system architecture</i>	63
Figure 7.3: <i>Project setup</i>	64